



constructive solutions

Fosroc Solvent 102

Resin cleaning solvent

Fosroc Solvent 102 is ideal for dissolving various types of industrial resin - epoxy, polyurethane, etc. It can be used as a cleaner for tools, containers and substrate.

Fosroc Solvent 102 is a specially developed solvent blend for use to clean resins commonly found in Fosroc solvent based products and other construction chemicals, and is much more effective than common solvents such as petrol, xylene, white spirit, heavy-naphtha, etc.

Application

For cleaning tools, it is best to pour some Fosroc Solvent 102 into a container and to clean the implements within this container.

For cleaning substrates, the solvent can be poured directly, or applied by cloth or paper.

Properties

Appearance	: Transparent, mobile liquid
------------	------------------------------

Specific gravity	: 0.9
------------------	-------

Limitations

Note: Using Solvent 102 as thinner can result in unfavourable side effects such as sagging, patchy finishes, lower gloss, not drying & low performance of the finished product. For further information please contact your local Fosroc office.

Storage

Shelf life

24 months if stored in the original unopened packs in a cool dry place. Do not store in direct sunlight.

Precautions

Health and safety

Solvent 102 is very harmful if swallowed or inhaled and may cause skin and eye irritation.

Should accidental skin contact occur, remove contaminated clothing and wash with warm soapy water. Do not scrub.

If inhaled remove person to fresh air. Get medical advice if breathing becomes difficult. In case of contact with eyes, rinse immediately with plenty of clean water for at least 15 minutes and seek medical advice. If swallowed, give a glass of water to dilute and seek medical attention immediately - do not induce vomiting. For further information, refer to the appropriate Product Material Safety Data Sheet.

Fire

Solvent 102 is highly flammable liquid. Keep away from sources of ignition. No smoking. Containers should be tightly sealed when not in use. In the event of fire, extinguish with CO₂ or foam. Do not use water jet.

Disposal

Dispose according to local authority regulations. Do not dispose down drains or into local waterways.

For further information on any of the above, please consult your local Fosroc office - as below.

Additional information

Flash point	: 23°C
-------------	--------

Packing	: 5 ltr
---------	---------

For further info please contact your local Fosroc office.

Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Service. **All Fosroc datasheets are updated on a regular basis. It is the user's responsibility to obtain the recent version.**

Head Office

telephone: (+9714) 2039699

fax: (+9714) 2859649

email: aqf@fosroc.com

Regional offices

Abu Dhabi, Al Gurg Fosroc
Bahrain, YBA Kanoo
Kuwait, Boodai
Oman, Al Amara

telephone: 673 1779
telephone: 17738200
telephone: 4817618
telephone: 24815080

fax: 673 1449
fax: 17732828
fax: 4832124
fax: 2481755

email: abudhabi@fosroc.com
email: bahrain@fosroc.com
email: kuwait@fosroc.com
email: oman@fosroc.com



Al Gurg Fosroc Co. LLC

Post Box 657, Dubai
United Arab Emirates

www.fosroc.com

UAE/0748/15/C