

Tristone ACRYLIC SOLID SURFACES

www.tristonesurfaces.com



WHO WE ARE

ABOUT TRISTONE

Tristone, represented by Mac Al Gurg in the UAE produces quartz and acrylic surfaces. Established in Korea in 1973, Tristone is an industry leader with certified technology, contemporary designs, dedicated research and development and fast-paced expansion into global markets.

ABOUT MAC AL GURG

Mac Al Gurg has been operating in the UAE's building and construction industry since 1974, being actively involved in many prestigious projects within the region. The company's constant endeavour is to deliver value-added products procured from leading manufacturers predominantly from the UK, Europe and America.



FEATURES

MATERIAL CHOICES

We abide by materials that are non-hazardous and have ecofriendly value, with certifications from NSF, Green Guard and more.

COLOURS & PATTERNS

Our portfolio includes a wide range of shades from white colours to high quality patterns. We offer aesthetically appealing and practical space options through customised designs.

DURABILITY


We offer high grade materials and technology, superior to natural marble in impact and scratch resistance. Our products are also free from bacteria, blotch and contamination.

FABRICATION ABILITY


Our fabrication process is similar to wood processes and can be thermoformed and produced for based on the client's requirements.

TEXTURES 8

GENERAL SERIES




PREMIUM SERIES




COLOURS

VEIN SERIES



SPECIAL SERIES



SOLID SERIES (ACRYLIC)



PEARL SERIES



PRODUCT APPLICATIONS

RESIDENTIAL

Kitchen top, residential sink bowls, bath tubs and wash basins, living spaces and furniture.

COMMERCIAL

Public buildings and office spaces, facades and wall cladding, shops and exhibitions, healthcare and hospitals, educational institutions, hotels and airports.






PRODUCT SPECIFICATIONS

SPECIFICATIONS

ITEM	UNIT	SPECIFICATION	
Thickness	mm	3.0, 6.0, 10.0, 12.0, 19.0	
Length	mm	2500, 3070, 3680	
Width	mm	760, 930, 1350, 1520	

^{*}Various sizes available upon request



PERFORMANCE PROPERTIES

UNIT	RESULTS	TEST METHOD
-	1.75	ASTM D792-13 (Method A)
-	90	ASTM D785-08 (Procedure A - 2015)
Мра	31.6	ASTM D638-14 (*)
Gpa	9.93	ASTM D638-14 (*)
Мра	62.8	ASTM D790-10 (**)
Gpa	10.0	ASTM D790-10 (**)
J/m	16	ASTM D256-10 (Method A)
%	0.03	ASTM D570-98
-	>95	NEMA LD3
-	No effect	NEMA LD3
°C	96	ASTM D648-07 (Method B)
	- Mpa Gpa Mpa Gpa J/m % -	- 1.75 - 90 Mpa 31.6 Gpa 9.93 Mpa 62.8 Gpa 10.0 J/m 16 % 0.03 - >95 - No effect

GENERAL TERMS & CONDITIONS

Lion Chemtech Co. Ltd. will warrant its solid surface materials against manufacture defects for the period of 10 years from the shipment date. This limited 10 year warranty against defective materials only applies to Lion Chemtech's solid surface products, which are stored, handles, fabricated, installed and used in the manner recommended in the Lion Chemtech fabrication manual, care and maintenance guide, technical bulletins and other standards that are known in the solid surface industry.

Head Office Email Phone

Al Gurg Tower 1, 2nd Floor, enquiry@macalgurg.com 800263

Baniyas Road, Dubai, UAE.