JOMOO (Xiamen) Construction Materials Co., Ltd

Add: 16th F, Bld. 30, Taizhong Road, Liangian Street, Siming District, Xiamen City, China

E-mail: service@jomoogroup.com Website: www.jomoogroup.com

TECHNICAL DATA SHEET

Category Freestanding Smart Toilet

Name of Product Freestanding Smart Toilet

Model ZD9830-S2-CJM000

Finish White



Dimensions

Dimensions: 781*485*546mm Flush way: Dumping System Drainage mode: S trap Rough in: Adjustable Rated voltage: 220V~ Rated frequency: 50Hz Rated power: 780W

Ma*imum input power: 1080W Ambient temperature: 0°C~40°C

Water pressure requirement: 0.05MPa (Flow pressure) - 0.75MPa

(Static pressure)

Inlet water temperature: 3°C~35°C

Waterproof rating: IP*4

Water temperature range: 30°C~ 41°C

Water heating power: 1000W

Seat temperature range: Room temperature to 41°C

Seat heating power: 60W Ma*imum air speed: ≥ 4m/s Warm air dryer power: 350W

Accessories include angle valve and filter, blowing agent, remote

control

Description

Cistern

Control type: Side button control+ Remote control+ Voice

Control

Seat & Lid Open Method: Microwave sensor, Remote control, Voice Control, App control, Waving control Flushing type: Remote Control Flush, Off-seat Auto

Flush, Power Outage Flush, Smart Dual Flush

Basic Functions: Rare Wash, Front Wash, Movable Massage Wash, Wide Clean Wash, Promoting Wash, Aerated Comfortable Wash, Warm Air Dryer, Heated Seat, Water Pressure&Water Temperature& Seat Temperature&Wash Position&Wind Temperaturecan be adjusted, Soft-close PP

seat, Anti-scald function, Bowl Pre-wetting

Other Functions: Bactericidal foam, Auto-adjust Seat Temperature, Touchless Control0, Anti-bacterial Seat, Selfcleaning nozzle, Anti-bacterial Nozzle, Removable nozzles, Smart Night Light, Smart Digital Display, Power Outage Flush, Battery box charge reminder, UI Light, Ultra silent flushing system

Glazed material: Rare earth antibacterial glaze

Technical drawing



