

TECHNICAL DATA SHEET

Category	Freestanding Smart Toilet	
Name of Product	Smart Toilet	
Model	ZD8920-SA-IDO305	
Finish	-	
Dimensions	Description	

Dimensions: L761*W422*H500mm
Flush way: Siphon
Drainage mode: S trap
Rough in : 305mm (S Trap)
Rated voltage: 220V~
Rated frequency: 50Hz
Rated power: 780W
Maximum input power: 1080W
Ambient temperature: 0°C~40°C
Water pressure requirement: 0.05MPa (Flow pressure) - 0.75MPa (Static pressure)
Inlet water temperature: 3°C~35°C
Waterproof rating: IPX4
Water temperature range: 30°C~ 41°C
Water heating power: 1000W
Seat temperature range: Room temperature to 41°C
Seat heating power: 60W
Maximum air speed: ≥ 4m/s
Warm air dryer power: 350W
Accessories include angle valve和filter、Blowing agent、remote control

Cistern
Control type: Side button control+ Remote control
Seat & Lid Open Method: Microwave sensor、 Remote control
Flushing type: Remote Control Flush、 Off-seat Auto Flush、 Power Outage Flush、 Smart Dual Flush
Basic function: Rare Wash、 Front Wash、 Movable Massage Wash、 Wide Clean Wash、 Promoting Wash、 Aerated Comfortable Wash、 Warm Air Dryer、 Heated Seat、 Water Pressure&Water Temperature& Seat Temperature&Wash Position&Wind Temperaturecan be adjusted、 Soft-close PP seat、 Anti-scald function、 Bowl Pre-wetting
Upgrade function: Bactericidal foam3.0、 Auto-adjust Seat Temperature、 Touchless Control3.0、 Anti-bacterial Seat、 Self-cleaning nozzle、 Anti-bacterial Nozzle、 Removable nozzles、 Smart Night Light、 Smart Digital Display、 Power Outage Flush、 Battery box charge reminder、 UI Light
Glazed material: Rare earth antibacterial glaze
Rimmed inner bowl

Technical drawing

