

System 2000


Fittings for PE and PVC pipes

Ø pipe A	L	E	B	Weight
63	171	80	124	3,6
75	175	82	138	4,3
90	181	85	152	5,8
110	181	85	172	6,5
125	185	87	193	8,2
140	197	93	210	9,0
160	221	105	236	11,8
180	241	113	258	19,0
200	261	125	284	24,0
225	265	128	314	28,0
250	300	145	347	34,0
280	306	148	376	40,5
315	358	174	422	62,5
355	464	237	472	98,0
400	506	237	520	112,0
450	544	262	566	142,0
500	720	350	675	216,0
560	770	375	730	273,0
630	823	400	820	358,0

DN	Ø pipe A	L	E	H	H1	Weight
80	90	210	85	110	165	12,7
80	110	223	85	110	165	14,2
100	110	223	85	125	180	16,0

Ø pipe A	L	E	B	Weight
63	106	80	124	2,7
75	138	82	138	3,2
90	141	85	152	4,6
110	159	85	172	6,4
125	162	87	193	6,1
140	169	93	210	7,7
160	180	105	236	8,6
180	192	113	258	11,7
200	203	125	284	14,5
225	207	128	314	16,5
250	225	145	347	20,5
280	228	148	376	25,0
315	254	174	422	33,5


Connector No. 0430



Caution! When using as coupling valve: **remove stop ring** and steeply chamfer pipe (see assembly instructions)

Order No.	MOP (PN)	Dimension Ø pipe A									
		63	75	90	110	125	140	160	180	200	225
0430	16										
		250	280	315	355	400	450	500	560	630	


Duck foot bend No. 5045



Optionally with or without axial thread outlet 2", No. 5047

Order No.	MOP (PN)	Dimension/DN Ø pipe A		
		80 90	80 110	100 110
5045	16			

End cap No. 8075



Optionally with or without axial or radial thread outlet 1" — 2"

Order No.	MOP (PN)	Dimension Ø pipe A											
		63	75	90	110	125	140	160	180	200	225	250	280
8075	16												