Edit R Wall Mounted WC Pan

ILLUSTRATED

S0794 Edit R Wall Mounted WC Pan

S0798 Edit R Toilet Seat and Cover - soft close

S0767 Oleas M2 mechanical dual flushplate Armitage Shanks -

chrome

R0153 ProSys 1150mm height, mechanical wall hung WC frame,

120 depth, front actuation

OPTIONS

R0099	ProSys electronic conversion kit for infra-red actuated flushplates (Septa Pro E1 & E2) (120 depth frames and cisterns only)		
S3326	Conceala 3 dual flush 6/4 litre cistern, side inlet, pneumatic actuation, easy adjustable to low water volumes (4.5/3 or 4/2.6 litres), internal overflow, flushpipe included, no button/flushplate		
E4463	Karisma pneumatic flush plate, dual flush, unbranded for Conceala 3 cisterns		
S0858	Septa Pro M1 mechanical metal dual flushplate Armitage Shanks		
S0772	Septa Pro E1 electronic (infrared) & manual metal dual flushplate Armitage Shanks		
S0773	Septa Pro E2 electronic (infrared) metal dual flushplate Armitage Shanks		
S1082	Conceala 3 dual flushplate		
E0060	Support frame with bolts for wall mounted toilet bowls		

ILLUSTRATED PRODUCT DETAILS

Weights		Finishes	Finishes	
S0794	21.10 KG	S0794	White (01)	
S0798	2.30 KG			
S0767	0.34 KG	S0798	White (01)	
R0153	12.20 KG			
Materials		S0767	Chrome (AA)	
S0794	Vitreous China			
S0798	Plastic	R0153	Neutral/No Finish	
S0767	Mixed Material		(67)	
R0153	Mixed Material	Designer		
		Robin Levi	en, RDI	

FINISH OPTIONS




Standards

Vitreous china to BS3402. WC pan to BS EN 997 and BS EN 33

Special Notes

Fix the E0060 support brackets to the floor within the duct and secure the WC with bolts (supplied) and hidden fixing set provided. Screw the bolts





FEATURES







Edit R Wall Mounted WC Pan

to the back wall. The bowl should not be installed with lever activated cistern fixed with syphon. Drawing shows the bowl with a Conceala 2 cistern and support brackets, heights may be different when used with a Prosys frame. Oleas, Solea, Altes & Symfo are compatible with Prosys cisterns only. Please see flushplate section for full finish/colour options.

